

Toluene**AH347-4**

Version 1.1 1

Revision Date 08/24/2017

Print Date 08/24/2017

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Toluene

SDS Number : 000000011441

Product Use Description : Solvent

Manufacturer or supplier's details : CHEM-SUPPLY Pty Ltd
38-50 Bedford St.
Gillman SA 5013, Australia

For more information call : +61 8 8440 2000
(Monday-Friday, 9:00am-5:00pm)

In case of emergency call : Medical: 1-800-498-5701 or +1-303-389-1414
: **Transportation (CHEMTREC): 1-800-424-9300 or +1-703-527-3887**
:
: **CHEMTREC in Australia: +(61)-290372994**
: (24 hours/day, 7 days/week)

2. HAZARDS IDENTIFICATION**Classification of the substance or mixture**

Classification of the substance or mixture : Flammable liquids, Category 2
Skin irritation, Category 2
Reproductive toxicity, Category 2
Specific target organ toxicity - single exposure, Category 3
Specific target organ toxicity - repeated exposure, Category 2,
Central nervous system, Liver, Kidney
Aspiration hazard, Category 1

GHS Label elements, including precautionary statements

Symbol(s) :



Toluene**AH347-4**

Version 1.1 1

Revision Date 08/24/2017

Print Date 08/24/2017

Signal word	: Danger
Hazard statements	: Highly flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness and dizziness. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.
Precautionary statements	: Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Response: IF SWALLOWED: Immediately call a POISON CENTER/doctor. IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF exposed or concerned: Get medical advice/ attention. Do NOT induce vomiting. If skin irritation occurs: Get medical advice/ attention. Take off contaminated clothing and wash before reuse. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction. Storage: Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up. Disposal: Dispose of contents/ container to an approved waste disposal plant.

Toluene**AH347-4**

Version 1.1 1

Revision Date 08/24/2017

Print Date 08/24/2017

3. COMPOSITION/INFORMATION ON INGREDIENTSFormula : C₇H₈

Chemical nature : Substance

CAS-No. : 108-88-3

Hazardous components

Chemical name	CAS-No.	Concentration
Toluene	108-88-3	<= 100%

4. FIRST AID MEASURES

Inhalation : Call a physician immediately.
Remove to fresh air.
If not breathing, give artificial respiration.
If breathing is difficult, give oxygen.
Use oxygen as required, provided a qualified operator is present.

Skin contact : Wash off immediately with plenty of water for at least 15 minutes.
Take off contaminated clothing and shoes immediately.
Wash contaminated clothing before re-use.
Call a physician.

Eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Call a physician immediately.

Ingestion : Do not induce vomiting without medical advice.
If a person vomits when lying on his back, place him in the recovery position.
Call a physician immediately.
Never give anything by mouth to an unconscious person.

Notes to physician : Treat symptomatically.

Toluene**AH347-4**

Version 1.1 1

Revision Date 08/24/2017

Print Date 08/24/2017

5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Foam
Carbon dioxide (CO₂)
Dry chemical
Cool closed containers exposed to fire with water spray.
- Unsuitable extinguishing media : Do not use a solid water stream as it may scatter and spread fire.
- Specific hazards during firefighting : Highly flammable.
Vapours may form explosive mixtures with air.
Vapours are heavier than air and may spread along floors.
Vapors may travel to areas away from work site before igniting/flashing back to vapor source.
In case of fire hazardous decomposition products may be produced such as:
Carbon monoxide
Carbon dioxide (CO₂)
- Special protective equipment for firefighters : Wear self-contained breathing apparatus and protective suit.
- Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- : HAZCHEM CODE: 3YE

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions : Wear personal protective equipment.
Immediately evacuate personnel to safe areas.
Keep people away from and upwind of spill/leak.
Ensure adequate ventilation.
Remove all sources of ignition.
Do not swallow.
Do not breathe vapours or spray mist.
Avoid contact with skin, eyes and clothing.
- Environmental precautions : Prevent further leakage or spillage if safe to do so.
Prevent product from entering drains.
Discharge into the environment must be avoided.
Do not flush into surface water or sanitary sewer system.
Do not allow run-off from fire fighting to enter drains or water courses.
- Methods for cleaning up : Ventilate the area.

Toluene**AH347-4**

Version 1.1 1

Revision Date 08/24/2017

Print Date 08/24/2017

No sparking tools should be used.
Use explosion-proof equipment.
Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

7. HANDLING AND STORAGE**Handling**

Advice on safe handling : Wear personal protective equipment.
Use only in well-ventilated areas.
Keep container tightly closed.
Do not smoke.
Do not swallow.
Do not breathe vapours or spray mist.
Avoid contact with skin, eyes and clothing.

Advice on protection against fire and explosion : Keep away from fire, sparks and heated surfaces.
Take precautionary measures against static discharges.
Ensure all equipment is electrically grounded before beginning transfer operations.
Use explosion-proof equipment.
Keep product and empty container away from heat and sources of ignition.
No sparking tools should be used.
No smoking.

Storage

Requirements for storage areas and containers : Store in area designed for storage of flammable liquids.
Protect from physical damage.
Keep containers tightly closed in a dry, cool and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Keep away from heat and sources of ignition.
Keep away from direct sunlight.
Store away from incompatible substances.
Container hazardous when empty.
Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

Further information on storage conditions : Keep containers tightly closed in a cool, well-ventilated place.
Keep away from heat and sources of ignition.
Keep away from direct sunlight.

Toluene**AH347-4**

Version 1.1 1

Revision Date 08/24/2017

Print Date 08/24/2017

Materials to avoid : Strong oxidizing agents, Strong acids and strong bases, May attack many plastics, rubbers and coatings.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Components with workplace control parameters**

Components	CAS-No.	Value	Control parameters	Update	Basis
Toluene	108-88-3	STEL : Short Term Exposure Limit (STEL):	150 ppm 574 mg/m ³	12 2011	AU NOEL: Australia. National Workplace OELs (Workplace Exposure Standards for Airborne Contaminants, Appendix A)
		TWA : Time Weighted Average (TWA):	50 ppm 191 mg/m ³	12 2011	AU NOEL: Australia. National Workplace OELs (Workplace Exposure Standards for Airborne Contaminants, Appendix A)
		SKIN_DES : Skin designation:	Can be absorbed through the skin.	12 2011	AU NOEL: Australia. National Workplace OELs (Workplace Exposure Standards for Airborne Contaminants, Appendix A)
		SKIN_DES : Skin designation:	Can be absorbed through the skin.	08 2005	AU OEL: Australia. OELs. (Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment)
		TWA : Time Weighted Average (TWA):	50 ppm 191 mg/m ³	08 2005	AU OEL: Australia. OELs. (Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment)
		STEL : Short Term Exposure Limit	150 ppm 574 mg/m ³	08 2005	AU OEL: Australia. OELs. (Adopted National Exposure Standards for

Toluene**AH347-4**

Version 1.1 1

Revision Date 08/24/2017

Print Date 08/24/2017

		(STEL):			Atmospheric Contaminants in the Occupational Environment)
--	--	---------	--	--	--

Engineering measures

Use with local exhaust ventilation.
Prevent vapour buildup by providing adequate ventilation during and after use.

Personal protective equipment

- Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.
For rescue and maintenance work in storage tanks use self-contained breathing apparatus.
Use NIOSH approved respiratory protection.
- Hand protection : Solvent-resistant gloves
Gloves must be inspected prior to use.
Replace when worn.
- Eye protection : Do not wear contact lenses.
Wear as appropriate:
Safety glasses with side-shields
If splashes are likely to occur, wear:
Goggles or face shield, giving complete protection to eyes
- Skin and body protection : Wear as appropriate:
Solvent-resistant apron
Flame retardant antistatic protective clothing.
If splashes are likely to occur, wear:
Protective suit
- Hygiene measures : When using do not eat, drink or smoke.
Wash hands before breaks and immediately after handling the product.
Keep working clothes separately.
Remove and wash contaminated clothing before re-use.
Do not swallow.
Do not breathe vapours or spray mist.
Avoid contact with skin, eyes and clothing.
This material has an established AIHA ERPG exposure limit.
The current list of ERPG exposure limits can be found at
http://www.aiha.org/insideaiha/GuidelineDevelopment/ERPG/Documents/2011erpgweelhandbook_table-only.pdf.
- Protective measures : Ensure that eyewash stations and safety showers are close to the workstation location.

Toluene**AH347-4**

Version 1.1 1

Revision Date 08/24/2017

Print Date 08/24/2017

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	: liquid
Colour	: colourless
Odour	: sweet pungent
pH	: Note: Not applicable
Melting point/range	: -95 °C
Boiling point/boiling range	: 110.6 °C
Flash point	: 39 °F (4 °C) Method: closed cup
Lower explosion limit	: 1 %(V)
Upper explosion limit	: 7.1 %(V)
Vapour pressure	: 38 hPa at 25 °C(77 °F)
Vapour density	: 3.1 Note: (Air = 1.0)
Density	: 0.867 g/cm ³ at 20 °C
Water solubility	: 0.74 g/l at 20 °C
Ignition temperature	: 480 °C

Toluene**AH347-4**

Version 1.1 1

Revision Date 08/24/2017

Print Date 08/24/2017

Decomposition temperature : Note: No decomposition if used as directed.

Molecular weight : 92.14 g/mol

10. STABILITY AND REACTIVITY

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Hazardous polymerization does not occur.

Conditions to avoid : Heat, flames and sparks.
Keep away from direct sunlight.

Incompatible materials to avoid : Strong oxidizing agents
Strong acids and strong bases
May attack many plastics, rubbers and coatings.

Hazardous decomposition products : In case of fire hazardous decomposition products may be produced such as:
Carbon monoxide
Carbon dioxide (CO₂)

11. TOXICOLOGICAL INFORMATION

Acute oral toxicity : LD50: 2,600 - 7,500 mg/kg
Species: Rat

Acute inhalation toxicity : LC50: 8800 ppm
Exposure time: 4 h
Species: Rat

Acute dermal toxicity : LD50: 12,124 mg/kg
Species: Rabbit

Skin irritation : Species: Rabbit
Result: Irritating to skin.

Toluene**AH347-4**

Version 1.1 1

Revision Date 08/24/2017

Print Date 08/24/2017

Eye irritation	: Species: Rabbit Result: slight irritation Method: OECD Test Guideline 405
Repeated dose toxicity	: Species: Rat Application Route: Inhalation Exposure time: 15 Weeks Note: Chronic toxicity 2500 ppm Based on experimental results, may cause adverse health effects on the following: Heart Liver Kidney Urinary tract Bladder
Genotoxicity in vitro	: Test Method: Ames test Result: negative : Test Method: Chromosome aberration test in vitro Cell type: Chinese Hamster Ovary Cells Result: negative
CMR effects	: Teratogenicity: Some evidence of adverse effects on development, based on animal experiments.

12. Ecological information**Toxicity**

Toxicity to fish	: LC50: 36.2 mg/l Exposure time: 96 h Species: Pimephales promelas (fathead minnow) : LC50: 13 mg/l Exposure time: 96 h Species: Lepomis macrochirus (Bluegill sunfish)
Toxicity to daphnia and other aquatic invertebrates	: LC50: 313 mg/l Exposure time: 48 h Species: Daphnia magna (Water flea)
Toxicity to algae	: LC50: > 100 mg/l

Toluene**AH347-4**

Version 1.1 1

Revision Date 08/24/2017

Print Date 08/24/2017

Exposure time: 24 h
Species: Algae

Toxicity to bacteria : EC50: 19.7 mg/l
Exposure time: 0.5 h
Species: Photobacterium phosphoreum

Other adverse effects

Additional ecological information : Bioaccumulation is unlikely.
Harmful to aquatic organisms.

13. DISPOSAL CONSIDERATIONS

Product : In accordance with local and national regulations.

14. TRANSPORT INFORMATION**ADR**

UN/ID No. : UN 1294
Description of the goods : TOLUENE
Class : 3
Packing group : II
Classification Code : F1
Hazard Identification Number : 33
Labels : 3

ADG ROAD

UN/ID No. : UN 1294
Description of the goods : TOLUENE
Class : 3
Packing group : II
Hazard Identification Number : 33
Labels : 3

IATA

UN/ID No. : UN 1294
Description of the goods : Toluene

Toluene**AH347-4**

Version 1.1 1

Revision Date 08/24/2017

Print Date 08/24/2017

Class : 3
Packing group : II
Labels : 3
Packing instruction (cargo aircraft) : 364
Packing instruction (passenger aircraft) : 353
Packing instruction (passenger aircraft) : Y341

IMDG

UN/ID No. : UN 1294
Description of the goods : TOLUENE
Class : 3
Packing group : II
Labels : 3
EmS Number 1 : F-E
EmS Number 2 : S-D

Marine pollutant : no

HAZCHEM CODE: 3YE

15. REGULATORY INFORMATION**National regulatory information**

Standard for the Uniform : Schedule 6
Scheduling of Medicines and
Poisons

Other international regulations**Notification status**

US. Toxic Substances : On TSCA Inventory
Control Act

Australia. Industrial Chemical : On the inventory, or in compliance with the inventory
(Notification and
Assessment) Act

Canada. Canadian : All components of this product are on the Canadian DSL
Environmental Protection Act
(CEPA). Domestic
Substances List (DSL)

Toluene**AH347-4**

Version 1.1 1

Revision Date 08/24/2017

Print Date 08/24/2017

Japan. Kashin-Hou Law List : On the inventory, or in compliance with the inventory

Korea. Existing Chemicals Inventory (KECI) : On the inventory, or in compliance with the inventory

Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act : On the inventory, or in compliance with the inventory

China. Inventory of Existing Chemical Substances : On the inventory, or in compliance with the inventory

NZIOC - New Zealand : On the inventory, or in compliance with the inventory

16. OTHER INFORMATION**Sources of key data used to compile the Safety Data Sheet:**

1. National Code of Practice for the Preparation of Material Safety Data Sheets 2nd Edition [NOHSC:2011(2003)]
2. Approved Criteria for Classifying Hazardous Substances [NOHSC:1008(1999)]
3. List of Designated Hazardous Substances [NOHSC:10005(1999)]
4. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995)]
5. Australian Dangerous Goods Code, No. 6 [National Road Transport Commission]
6. Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP), No. 19 [NDPSC: 2004]
7. National Code of Practice for the Labelling of Workplace Substances [NOHSC:2012(1994)]

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Final determination of suitability of any material is the sole responsibility of the user.

This information should not constitute a guarantee for any specific product properties.

Toluene

AH347-4

Version 1.1 1

Revision Date 08/24/2017

Print Date 08/24/2017

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

Prepared by:

Honeywell Performance Materials and Technologies Product Stewardship Group

End of Safety Data Sheet