

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1 Product identifier**

Product name 2, 2, 4 – TRIMETHYLPENTANE  
CAS-No. 540-84-1  
Product code AR1206, GP1206, IR1206, LC1206, PC1206, RP1206

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

Identified uses Chemical for analysis and production.

**1.3 Details of the supplier of the safety data sheet**

Company Chem-Supply Pty Ltd  
38 - 50 Bedford Street, Gillman SA 5013 Australia  
Telephone number (08) 8440 2000  
Fax number (08) 8440 2001

**1.4 Emergency Telephone Number**

Emergency phone  
Monday - Friday 8:30am - 5:00pm ACST (08) 8440 2000  
After hours: CHEMCALL 1800127406 / +6449179888

**1.5 Manufacturer**

Company RCI LABSCAN LIMITED.  
24 Rama 1 Road, Pathumwan, Bangkok 10330 Thailand

**SECTION 2: Hazards identification**

**2.1 Classification of the substance or mixture**

**Classification according to WHS Regulations (Australia)**

Flammable liquids (Category 2), H225  
Skin irritation (Category 2), H315  
Specific target organ toxicity - single exposure (Category 3), H336  
Aspiration hazard (Category 1), H304  
Acute aquatic toxicity (Category 1), H400  
Chronic aquatic toxicity (Category 1), H410  
For the full text of the H-Statements mentioned in this Section, see Section 16.

**Classification according to EU Directives 67/548/EEC or 1999/45/EC**

F	Highly flammable	R11
Xi	Irritant	R38
Xn	Harmful	R65
		R67
N	Dangerous for the environment	R50/53

For the full text of the R-phrases mentioned in this Section, see Section 16.

**2.2 Label elements**

Pictogram



Signal word

Danger

## Hazard statement(s)

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H410	Very toxic to aquatic life with long lasting effects.

## Precautionary statement(s)

P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing vapours.
P264	Wash hand thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/eye protection/face protection.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P303 + P361 + P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312	Call a POISON CENTER or doctor/physical if you feel unwell.
P331	Do NOT induce vomiting.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P362	Take off contaminated clothing and wash before reuse.
P391	Collect spillage.
P370 + P378	In case of fire: Use carbon dioxide, dry chemical or foam for extinction.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

**2.3 Other hazards** None

### SECTION 3: Composition/information on ingredients

#### 3.1 Substances

Synonyms Isooctane, Isobutyltrimethylpentane.

CAS-No	EC-No	EC-Index-No	Formula	Molecular Weight	Weight %
540-84-1	208-759-1	601-009-00-8	(CH <sub>3</sub> ) <sub>2</sub> CHCH <sub>2</sub> C(CH <sub>3</sub> ) <sub>3</sub>	114.23 g/mol	>99

#### Hazardous ingredients according to WHS Regulations (Australia)

Component	Concentration	Classification
<b>2, 2, 4-Trimethylpentane</b>		
CAS-No 540-84-1 EC-No 208-759-1 EC-Index-No 601-009-00-8	>99%	Flammable liquids (Category 2), H225 Skin irritation (Category 2), H315 Specific target organ toxicity - single exposure (Category 3), H336 Aspiration hazard (Category 1), H304 Acute aquatic toxicity (Category 1), H400 Chronic aquatic toxicity (Category 1), H410

**Hazardous ingredients according to Directive 1999/45/EC**

Component	Concentration	Classification
<b>2, 2, 4-Trimethylpentane</b>		
CAS-No 540-84-1 EC-No 208-759-1 EC-Index-No 601-009-00-8	>99%	F, Highly flammable, R11 Xi, Irritant, R38 Xn, Harmful, R65 R67 N, Dangerous for the environment, R50/53

For the full text of the H-Statements and R-Phrases mentioned in this Section, see Section 16

**SECTION 4: First aid measures****4.1 Description of first aid measures**

General advice	Show this safety data sheet to the doctor in attendance.
Inhalation	Move to fresh air in case of accidental inhalation of vapors. Keep patient warm. In case of shortness of breath, give oxygen. Apply artificial respiration only if patient is not breathing or under medical supervision. No artificial aspiration mouth to mouth or mouth to nose. Use suitable instruments/apparatus.
Skin contact	Remove contaminated clothing and wash affected skin with soap and water. If signs of poisoning appear, treat as for inhalation. Obtain medical attention. Wash contaminated clothing before reuse. Contaminated combustible material, e.g. clothing ignites more readily and burns fiercely.
Eye contact	If the substance has got into the eyes, immediately wash out with plenty of water at least 15 minutes. Obtain medical attention.
Ingestion	Rinse mouth. Do not induce vomiting. Keep patient warm. In case of shortness of breath, give oxygen. Apply artificial respiration only if patient is not breathing or under medical supervision. No artificial aspiration mouth to mouth or mouth to nose. Use suitable instruments/apparatus. Obtain medical attention. Never give anything by mouth to an unconscious person.

**4.2 Most important symptoms and effects, both acute and delayed**

The most important known symptoms and effects are described in section 2.2 and section 11

**4.3 Indication of any immediate medical attention and special treatment needed**

After swallowing, caution if victim vomits. Risk of aspiration. Keep airways free. In case of spontaneous vomiting: Risk of aspiration. Pulmonary failure possible. Call in physician.

**SECTION 5: Firefighting measures****5.1 Extinguishing media****Suitable extinguishing media**

Extinguish with carbon dioxide, dry chemical or foam. In the event of fire, cool tanks with water spray.

**5.2 Special hazards arising from the substance or mixture**

Vapors may form explosive mixture with air. Flash back possible over considerable distance.

**5.3 Advice for firefighters**

Wear self-contained breathing apparatus and protective suit.

**5.4 Hazchem Code**

3YE

### 5.5 Further information

Standard procedure for chemical fires. Take measures to prevent electrostatic charging. Prevent firefighting water from entering surface water or groundwater.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Evacuate personnel to safe areas. Do not breathe vapors or spray mist. Wear a positive-pressure supplied-air respirator, flame retardant antistatic protective clothing. Shut off leaks if without risk. Keep people away from and upwind of spill/leak.

### 6.2 Environmental precautions

Contain or absorb leaking liquid with sand or earth, consults an expert. Prevent liquid entering sewers, basements and workpits. If substance has entered a water course or sewer or contaminated soil, advise police.

### 6.3 Methods and materials for containment and cleaning up

Spillage: May react with combustible substances creating fire or explosion hazard and formation of toxic fumes. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Soak up with inert absorbent material (e.g. sand, silica gel). Prevent liquid entering sewers, basements and workpits; vapor may create explosive atmosphere. Transfer to covered steel drums. Dispose of promptly.

### 6.4 Reference to other sections

For disposal see **Section 13**.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Keep container tightly closed. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only in area provided with appropriate exhaust ventilation. Do not breathe vapors or spray mist. Avoid contact with skin, eyes and clothing. Do not empty into drains.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep tightly closed at room temperature in a dry, cool and well-ventilated place. Keep away from heat and sources of ignition. Keep out of direct sunlight and away from incompatible materials. Store in original container. Electrical equipment should be protected to the appropriate standard.

### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Exposure limit (Safe Work Australia)

Not Available

### 8.2 Exposure controls

#### Appropriate engineering controls

The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Ventilation hoods and fans required when working with organic solvents or in hot melt applications.

#### Individual protection measures (Personal protective equipment, PPE)

##### Eye/face protection

Goggles giving complete protection to eyes.

**Skin protection**

Chemical resistant apron / flame retardant antistatic protective clothing, heavy duty work shoes.

Handle with gloves

- Full contact wears gloves from nitrile rubber material.
- Splash contact wears gloves from polychloroprene material.

The select protective gloves have to satisfy the specifications of EU Directive 89/686 EEC and standard EN 374 derived from it.

**Respiratory protection**

In case of insufficient ventilation, wear suitable respiratory equipment. Required when vapor/aerosols are generated filter A (EN 141 or EN 14387).

**Environmental exposure controls**

Prevent liquid entering sewers, basements and workpits.

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties**

Appearance: From	Liquid
: Color	Colorless
Odour	Benzene-like
Odour Threshold	Not Available
pH	Neutral
Melting point/range	-107 °C
Boiling point/range	99°C at 1013 hPa
Flash point	-12 °C (closed cup)
Evaporation rate	Not Available
Flammability (solid, gas)	Not Available
Explosion limits: lower	1 % (V)
upper	6 % (V)
Vapor Pressure	51 hPa at 20°C
Relative Vapor Density	3.9
Density	0.690 g/ml at 20°C
Water solubility	0.56 g/l at 25°C
Partition coefficient (n-octanol/water)	log Pow: 4.09
Auto-Ignition temperature	410 °C
Decomposition Temperature	Not Available
Viscosity	0.50 mPa.s at 20°C
Explosive properties	Not Explosive
Oxidizing properties	The substance or mixture is not classified as oxidizing.

**SECTION 10: Stability and reactivity****10.1 Reactivity**

Highly inflammable. Unsuitable working materials: various plastics. Explosible with air in a vaporous/gaseous state.

**10.2 Chemical stability**

Stable under recommended storage conditions.

**10.3 Possibility of hazardous reactions**

The substance forms an explosive mixture with air.

**10.4 Conditions to avoid**

Heat, flames and sparks.

**10.5 Incompatible materials**

Strong oxidizing agents

**10.6 Hazardous decomposition products**

Carbon monoxides, Carbon dioxides (Hazardous decomposition products from under fire condition).

**SECTION 11: Toxicological information****11.1 Information on toxicological effects****Acute toxicity**

LD<sub>50</sub> (oral, rat): >2500 mg/kg

LC<sub>50</sub> (inhalation, rat): 37.5mg/l /4h

**Acute oral toxicity**

After accidental swallowing the substance may pose a risk of aspiration. Passage into the lung (vomiting) can result in a condition resembling pneumonia (chemical pneumonitis). Damage of lung.

**Acute inhalation toxicity**

Irritations of mucous membranes, drowsiness.

**Skin corrosion/irritation**

Irritations: degreasing effect on the skin, possibly followed by secondary inflammation.

**Serious eye damage/eye irritation**

Slight irritations.

**Respiratory or skin sensitization**

Not Available

**Germ cell mutagenicity**

Mutagenicity (mammal cell test): negative (in vitro).

**Carcinogenicity**

Not Available

**Reproductive toxicity**

Not Available

**Teratogenicity**

Not Available

**Specific target organ toxicity (STOT) - single exposure**

May cause drowsiness or dizziness.

**Specific target organ toxicity (STOT) - repeated exposure**

Not Available

**Aspiration hazard**

May cause pulmonary edema and pneumonitis.

**Further information**

Damage of lung.

The product should be handled with the care usual when dealing with chemicals.

## SECTION 12: Ecological information

### 12.1 Toxicity

Toxicity to fish	LC <sub>0</sub> L.idus: 500 mg/ l/ 48h.
Toxicity to bacteria	EC <sub>5</sub> Ps. Putida: 10000 mg/l.

### 12.2 Persistence and degradability

Biodegradability      Distribution preferentially in air.

### 12.3 Bioaccumulative potential

Partition coefficient (n-octanol/water)	log Pow: 4.09 (experimental)
	An appreciable Bioaccumulation potential is to be expected (log P o/w >3)

### 12.4 Mobility in soil

Not Available

### 12.5 Other adverse effects

Biological effects: High toxic for aquatic organisms. May cause long term adverse effects in the aquatic environment. Endangers drinking water supplies if swallowed to enter soil and or waters in large quantities. Do not allow to enter waters, waste water or soil.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Product

There are no uniform EC Regulations for the disposal of chemicals or residues. Chemical residues generally count as special waste. The disposal of the latter is regulated in the EC member countries through corresponding law and regulations. We recommend that you contact either the authorities in charge or approved waste disposal companies which will advise you on how to dispose of special waste or burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Observe all federal, state, and local environmental regulations.

#### Contaminated packaging

Disposal in compliance with official regulations. Handle contaminated packaging as hazardous waste in the same way of the substance itself. If not officially specified differently, non-contaminated packaging may be treated like household waste or recycled.

## SECTION 14: Transport information

### Land Transport (ADG Code)

UN Number	1262
UN proper shipping name	OCTANES
Transport hazard class(es)	3
Hazchem Code	3YE
Packing group	II
Environmental hazards	Yes
Special precautions for user	Yes

### Sea transport (IMDG)

UN Number	1262
UN proper shipping name	OCTANES
Transport hazard class(es)	3
Packing group	II
Marine pollutant	Yes
Special precautions for user	Yes

EmS F-E S-E

**Air transport (IATA)**

UN Number	1262
UN proper shipping name	OCTANES
Transport hazard class(es)	3
Packing group	II
Environmental hazards	Yes
Special precautions for user	No

**River transport (AND/ADNR)**

(Not examined)

## SECTION 15: Regulatory information

This safety datasheet complies with the requirements of Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

<b>Regulatory Information</b>	Listed in the Australian Inventory of Chemical Substances (AICS).
<b>Poisons Schedule</b>	S5

### 15.2 Chemical Safety Assessment

For this product a chemical safety assessment was not carried out.

## SECTION 16: Other information

### Full text of H-Statements referred to under sections 2 and 3

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

### Full text of R-phrases referred to under sections 2 and 3

F	Highly flammable.
Xi	Irritant
Xn	Harmful
N	Dangerous for the environment.
R11	Highly flammable.
R38	Irritating to skin.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65	Harmful: may cause lung damage if swallowed.
R67	Vapours may cause drowsiness and dizziness.

### Recommended restrictions

Take notice of labels and safety data sheets for the working. Chemicals Take necessary action to avoid static electricity discharge.

### Reference

Globally Harmonized System of Classification and Labelling of Chemicals (GHS).  
 Labelling according to Code of Practice for the Labelling of Workplace Hazardous Chemicals (Safe Work Australia).  
 Transportation information according to Recommendations on the Transport of Dangerous Goods, Model Regulations. Twelfth revised edition. United Nations.



Institute for Occupational Safety and Health of the German Social Accident Insurance in Sankt Augustin/Germany,  
Source: IFA for Databases on hazardous substances (GESTIS).

**Further information**

Contact Chem – Supply Pty Ltd Ph. (08) 8440 2000.

**Revision Date**

12/12/2017

---

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process unless specified in the text.