

CSAScientific CSAIngredients



Safety Data Sheet OG6 STAIN Solution

SDS no. JH52D6LH • Version 1.0 • Date of issue: 2025-02-03

SECTION 1: Identification

GHS Product identifier

Product name OG6 STAIN Solution

Product number 0G6

Recommended use of the chemical and restrictions on use

Laboratory reagent.

Supplier's details

Name ChemSupply Australia Pty Ltd Address 38-50 Bedford Street

5013 Gillman South Australia

Australia

Telephone 08 8440 2000

email www.chemsupply.com.au

National contact

Name Australian Biostain Pty Ltd Address 16 Shipwright Road

5016 Largs North SA

Australia

Emergency phone number

CHEMCALL 1800 127 406 (Australia) / +64-4-917-9888 (International)

SECTION 2: Hazard identification

General hazard statement

Dangerous goods of Class 3 (Flammable Liquid) are incompatible in a placard load with any of the following: Class 1, Class 2.1, if both the Class 3 and Class 2.1 dangerous goods are in bulk, Class 2.3, Class 4.2, Class 5, Class 6, if the Class 3 dangerous goods are nitromethane, Class 7.

Classification of the substance or mixture

GHS classification in accordance with: UN GHS revision 7

- Flammable liquids, Cat. 2

- Serious eye damage/eye irritation, Cat. 2A

GHS label elements, including precautionary statements

Pictograms



Signal word Danger

Hazard statement(s)

H225 Highly flammable liquid and vapor H319 Causes serious eye irritation

Precautionary statement(s)

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof [electrical/ventilating/lighting/...] equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.
P264 Wash hands thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use agents recommended in Section 5 of SDS for extinction

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container to an approved waste disposal facility

SECTION 3: Composition/information on ingredients

Mixtures

Components

Components		
Component	CAS no.	Concentration
Ethanol (EC no.: 200-578-6; Index no.: 603-002-00-5)	64-17-5	<= 80 % (weight)
CLASSIFICATIONS: Flammable liquids, Cat. 2. HAZARDS: H225 - Highly flammable liquid and vapor.		
Water (EC no.: 231-791-2)	7732-18-5	>= 18 % (weight)
CLASSIFICATIONS: No data available. HAZARDS: No data available.		
Orange G (EC no.: 217-705-6)	1936-15-8	< 1 % (weight)
CLASSIFICATIONS: No data available. HAZARDS: No data available.		
Acetic acid (EC no.: 200-580-7; Index no.: 607-002-00-6)	64-19-7	< 1 % (weight)
CLASSIFICATIONS: Flammable liquids, Cat. 3; Skin corrosion/irritation, Cat. 1A. HAZARDS: H226 - Flammable	liquid and vapor; H314 - C	auses severe skin burns and
eye damage. [SCLs/M-factors/ATEs]: Skin Corr. 1A; H314: $C \ge 90$ %; Skin Corr. 1B; H314: 25 % $\le C < 90$ %;	Skin Irrit. 2; H315: 10 % s	≤ C < 25 %; Eye Irrit. 2; H319:
10 % ≤ C < 25 %		
Phosphotungstic Acid (EC no.: 215-682-7)	1343-93-7	< 0.2 % (weight)
CLASSIFICATIONS: Serious eye damage/eye irritation, Cat. 1; Skin corrosion/irritation, Cat. 1B. HAZARDS: H31	4 - Causes severe skin bu	rns and eye damage; H318 -
Causes serious eve damage		

SECTION 4: First-aid measures

Description of necessary first-aid measures

General advice First Aid Facilities: Maintain eyewash fountain in work area.

If inhaled If inhaled, remove from contaminated area to fresh air immediately. Apply artificial

respiration if not breathing. If breathing is difficult, give oxygen. Get medical aid if

cough or other symptoms appear.

In case of skin contact Rinse with plenty of water. Get medical attention if irritation develops and persists.

In case of eye contact If contact with the eye(s) occurs, wash with copious amounts of water for

approximately 15 minutes holding eyelid(s) open. Take care not to rinse contaminated water into the non-affected eye. If persistent irritation occurs, obtain medical attention.

If swallowed Rinse mouth thoroughly with water immediately, repeat until all traces of product have

been removed. DO NOT INDUCE VOMITING. Seek medical advice if effects persist.

Most important symptoms/effects, acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

Indication of immediate medical attention and special treatment needed, if necessary

For advice, contact the National Poisons Information Centre (Phone Australia 13 11 26; New Zealand 0800 764 766) or a doctor.

SECTION 5: Fire-fighting measures

Suitable extinguishing media

Caution: Use of water spray when fighting fire may be inefficient.

Small fire: Use foam, dry chemical, CO2 or water spray.

Large fire: Use foam, fog or water spray - Do not use water jets.

If safe to do so, move undamaged containers from fire area. Cool containers with flooding quantities of water until well after fire is out.

Specific hazards arising from the chemical

Hazards from Combustion Products: Oxides of carbon.

FLAMMABLE: These products have a low flash point - Will be easily ignited by heat, sparks or flames at ambient temperatures. Vapours will form explosive mixtures with air. Vapours will travel to source of ignition and flash back. Fire may produce irritating, poisonous and/or corrosive gases. Containers may explode when heated. Many liquids are lighter than water. Many vapours are heavier than air and will collect in low or confined areas (drains, basements, tanks). Vapours from run-off may create an explosion hazard.

Special protective actions for fire-fighters

SCBA and structural firefighter's uniform may provide limited protection. Fully-encapsulating, gas-tight suits should be worn for maximum protection.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Evacuate the area of all non-essential personnel. Remove ignition sources Avoid inhalation, contact with skin, eyes and clothing.

Wear protective clothing specified for normal operations (see Section 8)

Methods and materials for containment and cleaning up

ELIMINATE all ignition sources (no smoking, flares, sparks or flame) within at least 50m - All equipment used in handling the product must be earthed. Do not touch or walk through spilled material. Stop leak if safe to do so - Prevent entry into waterways, drains or confined areas. Vapour-suppressing foam may be used to control vapours. Absorb spill with earth, sand or other non-combustible material - Use clean, non-sparking tools to collect material and place it in loosely-covered metal or plastic containers for later disposal. Water spray may be used to knock down or divert vapour clouds.

SEEK EXPERT ADVICE ON HANDLING AND DISPOSAL.

SECTION 7: Handling and storage

Precautions for safe handling

Avoid fumes.

Highly Flammable Material:-

Do not use near any source of ignition.

Use only in a well ventilated area.

No smoking or eating of food in area of use.

Keep containers tightly closed at all times.

Open containers slowly to avoid sudden pressure release.

Material will accumulate Static Charge, bulk containers should be electrically grounded.

Store in a cool dry place that is well ventilated and away from direct sunlight.

Storage for greater than minimal quantities must be in an Approved Flammable Material Cabinet.

Bulk Storage greater than 200 Litres must be in an Approved Bulk Storage Store, fully bunded and ventilated.

Empty containers must be filled with water and rinsed out before disposal or recommissioning.

Wear Safety glasses, gloves and protective apron.

Work in an area of good ventilation, an approved fume cupboard is preferred.

Ensure electrical devices are flash/flame proofed.

No eating or drinking in workplace, wash hands whenever leaving work area.

Conditions for safe storage, including any incompatibilities

Absorb or contain liquid with sand, earth or spill control material. Shovel up using non sparking tools and place in a labelled, sealable container for subsequent safe disposal. Put leaking containers in a labelled drum or overdrum.

SECTION 8: Exposure controls/personal protection

Control parameters

CAS: 64-17-5

Ethanol

AU/SWA (Australia): 1000 ppm; 1880 mg/m3 TWA inhalation

CAS: 64-19-7

Acetic acid

AU/SWA (Australia): 15 ppm; 37 mg/m3 STEL inhalation; 10 ppm; 25 mg/m3 TWA inhalation

Appropriate engineering controls

Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, gas, etc.) below recommended exposure limits.

Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection

SDS no. JH52D6LH • Version 1.0 • Date of issue: 2025-02-03

The use of a face shield, chemical goggles or safety glasses with side shield protection as appropriate. Must comply with Australian Standards AS 1337 and be selected and used in accordance with AS 1336.

Skin protection

Clean impervious clothing should be worn. Clothing for protection against chemicals should comply with AS 3765 Clothing for Protection Against Hazardous Chemicals.

Body protection

Footwear: Safety boots in industrial situations is advisory, foot protection should comply with AS 2210, Occupational protective footwear - Guide to selection, care and use.

Body Protection: Clean clothing or protective clothing should be worn, preferably with and apron. Clothing for protection against chemicals should comply with AS 3765 Clothing for Protection Against Hazardous Chemicals.

Respiratory protection

If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable vapor/ mist filter should be used. Refer to relevant regulations for further information concerning respiratory protective requirements. Reference should be made to Australian Standards AS/ NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

SECTION 9: Physical and chemical properties

Basic physical and chemical properties

Physical state Liquid

Appearance Thin, clear, volatile liquid.
Color Orange

Odor Alcoholic
Odor threshold No data available.

Melting point/freezing point No data available.

Boiling point or initial boiling point and boiling range ~85°C Flammability Highly Flammable

Lower and upper explosion limit/flammability limit Flammable Limits - Lower: 3.5% (100% ethanol) Flammable

Limits - Upper: 19% (100% ethanol)

Flash point 20°C

Explosive properties

Auto-ignition temperature

Decomposition temperature

Oxidizing properties

No data available.

Kinematic viscosity

No data available.

Solubility Solubility in Water: Miscible.

Partition coefficient n-octanol/water (log value)

Vapor pressure

No data available.

Evaporation rate

No data available.

No data available.

Density and/or relative density Specific Gravity: ~0.91 @ 20°C

Relative vapor density
Particle characteristics
No data available.
No data available.

Supplemental information regarding physical hazard classes

No data available.

Further safety characteristics (supplemental)

No data available.

SECTION 10: Stability and reactivity

Reactivity

Stable under normal conditions of storage and handling.

Risk of ignition. Vapours may form explosive mixtures with air

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

Vapours may form explosive mixture with air.

Hazardous Polymerization: Will not occur.

Conditions to avoid

Heat, sparks, flame and build-up of static electricity.

Incompatible materials

Oxidising agents, peroxides, strong acids, acid chlorides, acid anhydrides, alkali metals and ammonia.

Hazardous decomposition products

May liberate toxic fumes in fire producing carbon monoxide and or carbon dioxide.

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity

Acute Toxicity - Oral: LD50 (rat): 7060 mg/kg - Ethanol

Ingestion: May cause nausea, vomiting, headache, dizziness, gastric irritation and CNS depression. Over exposure to methanol can cause death or damage to kidneys, liver, lungs, eyes, brain and nervous system.

Inhalation: Irritating to the mucous membranes and respiratory tract. May cause headaches, dizziness, nausea and possible CNS effects.

Skin corrosion/irritation

May cause irritation. Will have a degreasing action on the skin.

Serious eye damage/irritation

May cause irritation and watering.

Respiratory or skin sensitization

Respiratory sensitisation: Not classified based on available information.

Skin Sensitisation: Not classified based on available information.

Germ cell mutagenicity

GG STAIN Solution SDS no. JH52D6LH • Version 1.0 • Date of issue: 2025-02-03

Safety Data Sheet OG6 STAIN Solution

Germ cell mutagenicity: Not classified based on available information.

Mutagenicity: Not classified based on available information.

Carcinogenicity

Ethanol [61-17-5] in alcoholic beverages are evaluated in the IARC Monographs (Vol. 96) as Group 1: Carcinogenic to humans, (based on effects of drinking alcoholic beverages).

Safe Work Australia does not classify ethanol as a carcinogen.

Reproductive toxicity

Not classified based on available information.

Specific target organ toxicity (STOT) - single exposure

Not classified based on available information.

Specific target organ toxicity (STOT) - repeated exposure

Not classified based on available information.

Aspiration hazard

Not classified based on available information.

Additional information

Health Hazard: Ethanol - Though it is rapidly oxidized in the body and is therefore non-cumulative, ingestion of even moderate amounts causes lowering of inhibitions, often succeeded by dizziness, headache, or nausea. Larger intake causes loss of motor nerve control, shallow respiration, and in extreme cases unconsciousness and even death. Degree of intoxication is determined by concentration of alcohol in the brain. Of primary importance is the fact that intake of moderate amounts together with barbiturates or similar drugs is extremely dangerous and may even be fatal.

Chronic Effects: Repeated or prolonged skin contact may cause chronic dermatitis. May cause liver and kidney disorders.

SECTION 12: Ecological information

Toxicity

Short Summary of Assessment of Environmental Impact: No ecological problems are to be expected when the product is handled and used with due care and attention.

SECTION 13: Disposal considerations

Disposal methods

Product disposal

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers.

Other disposal recommendations

Do not discharge this material into waterways, drains and sewers.

SECTION 14: Transport information

ADG (Road and Rail)

UN Number: 1993

Class: 3

Packing Group: II

SDS no. JH52D6LH • Version 1.0 • Date of issue: 2025-02-03

Proper Shipping Name: FLAMMABLE LIQUID, N.O.S. (Contains ETHANOL 80%)

Hazchem emergency action code (EAC)

•3YE

IMDG

UN Number: 1993

Class: 3

Packing Group: II

Proper Shipping Name: FLAMMABLE LIQUID, N.O.S. (Contains ETHANOL 80%)

IATA

UN Number: 1993

Class: 3

Packing Group: II

Proper Shipping Name: FLAMMABLE LIQUID, N.O.S. (Contains ETHANOL 80%)

SECTION 15: Regulatory information

Safety, health and environmental regulations specific for the product in question

Australia SUSMP Poison Schedule: S6

SECTION 16: Other information

Further information/disclaimer

ChemSupply Australia Pty Ltd does not warrant that this product is suitable for any use or purpose. The user must ascertain the suitability of the product before use or application intended purpose. Preliminary testing of the product before use or application is recommended. Any reliance or purported reliance upon ChemSupply Australia Pty Ltd with respect to any skill or judgement or advice in relation to the suitability of this product of any purpose is disclaimed. Except to the extent prohibited at law, any condition implied by any statute as to the merchantable quality of this product or fitness for any purpose is hereby excluded. This product is not sold by description. Where the provisions of Part V, Division 2 of the Trade Practices Act apply, the liability of ChemSupply Australia Pty Ltd is limited to the replacement of supply of equivalent goods or payment of the cost of replacing the goods or acquiring equivalent goods.

Preparation information

All information provided in this data sheet or by our technical representatives is compiled from the best knowledge available to us. However, since data, safety standards and government regulations are subject to change and the conditions of handling and use, or misuse, are beyond our control, we make no warranty either expressed or implied, with respect to the completeness or accuracy to the information contained herein. ChemSupply Australia Pty Ltd accepts no responsibility whatsoever for its accuracy or for any results that may be obtained by customers from using the data and disclaims all liability for reliance on information provided in this data sheet or by our technical representatives.

Standard for the Uniform Scheduling of Medicines and Poisons, Commonwealth of Australia

National Road Transport Commission, 'Australian Code for the Transport of Dangerous Goods by Road and Rail 7th. Ed.'

Safe Work Australia, 'National Code of Practice for the Preparation of Safety Data Sheets for Hazardous Chemicals', July 2020,

Safe Work Australia, 'National Guide for Classifying Hazardous Chemicals', July 2020.

Safe Work Australia, Workplace Exposure Standards for Airbourne Contaminants, December 2019

Safe Work Australia, Hazardous Chemical Information System (HCIS), hcis.safeworkaustralia.gov.au

IATA, Dangerous Goods Regulations (DGR)

IMO, International Maritime Dangerous Goods Code (IMDG)